

EATON

Powerware

FERRUPS® Rackmount 60 Hz

Unmatched reliability in configurable power protection for computers and telecommunications equipment



Product Snapshot

Rating:	850 VA - 7 kVA
Input Voltage:	120/208/240
Output Voltage:	120/208/240
Frequency:	60 Hz
Configuration:	Rackmount

Features

- Active Voltage Regulation converts power from almost any AC source into computer grade power
- Eliminates harmful harmonic currents from entering a building's wiring, where they can disrupt computer operations
- Enhanced diagnostics initiate automatic startup and scheduled tests on the logic board, battery and other critical systems
- Provides regulated output voltage without drawing power from batteries, keeping the batteries fully charged for unexpected blackouts
- Complete offering of LanSafe® power management software included to ensure data integrity
- Provides investment protection with a two-year limited warranty, 10-year, pro-rated warranty, \$250,000 load protection guarantee (U.S. and Canada)

Powerware FERRUPS® uninterruptible power systems furnish unmatched reliability in configurable power protection for computers and telecommunications equipment. Patented ferroresonant technology delivers "bulletproof" power protection, overcoming spikes, sags, surges, noise, and lightning. Powerware-exclusive SineSense provides clean, reliable power while conserving batteries during blackouts.

Extensive configurability options make FERRUPS the ideal power protection solution with a wide range of voltages, frequencies, runtimes, power cords, and receptacles. FERRUPS prevents the backfeed of harmonic currents into building wiring, which can disrupt computer operations. Redundant power paths assure high fault-tolerance and opti-

mum uptime. Galvanic isolation separates input from output, filtering line noise and surges.

FERRUPS also features precision voltage regulation with no battery discharge down to 38% below nominal (depending upon load); and over 80 user-programmable diagnostic and communications functions.

FERRUPS models include free Powerware Software Suite power management software with connectivity cable, and are BestLink SNMP/WEB-ready for remote management. FERRUPS covers up to US\$250,000 for damage to connected equipment resulting from a spike or surge (U.S. and Canada only).

Technical Specifications

Model		850 VA	1.4 kVA	2.1 kVA	3.1 kVA	7 kVA*
Model No.		FES850 VA	FES1.4 kVA	FER2.1 kVA	FER3.1 kVA	FER7 kVA
Capacity (kVA/kW)		.8/6	1.4/1	2.1/1.5	3.1/2.2	7/5
Dimensions	inches	9.75 x 16 x 21.25	9.75 x 16 x 21.25	9.75 x 16 x 26.25	9.75 x 16 x 26.25	19 x 16 x 26.25
H x W x D	mm	248 x 406 x 540	248 x 406 x 540	248 x 406 x 667	248 x 406 x 667	483 x 406 x 667
Front Panel	inches	10.5 x 19	10.5 x 19	10.5 x 19	10.5 x 19	19.25 x 19
H x W	mm	267 x 483	267 x 483	267 x 483	267 x 483	489 x 483
Battery Pack	inches	Internal	Internal	Internal	Internal	8.3 x 16.25 x 24.25
H x W x D	mm					211 x 413 x 616
Weight	lb	105	150	220	238	580
(includes batteries)	kg	48	68	100	108	263
Input - Hardwired Connection		120=10A	120=15A	120=25A	120=35A	120=65A
Circuit Breaker Requirement		208=5A	208=10A	208=15A	208=20A	208=40A
(Contact factory for powercord options.)		240=5A	240=10A	240=15A	240=15A	240=35A
Output Connection		Hardwired output is standard. Contact factory for receptacle options.				
Typical Runtime:	full load	11	14	24	14	12
(minutes)	half load	28	36	58	35	33

Operation

Nominal Input Voltage		120/208/240				
Input Voltage Range		+15%, -20%				
Operating Frequency		60 Hz (on-line - ± 0.01 Hz to ± 3 Hz adjustable, on inverter - ± 0.005 Hz)				
Nominal Output Voltage		120/208/240				
Output Voltage Regulation		$\pm 3\%$ for input voltages +15%, -20% of nominal. +5%, -8.3% for any line , load or battery condition.				
Output Voltage Waveform		Sine Wave				
Output Voltage		THD 5% or less THD at rated kW load				
Overload Capacity		150% surge and 125% for 10 minutes on-line. 150% surge and 110% for 10 minutes on inverter.				
Transfer Time		0 ms				
Lightning, Surge, and Noise Protection		2000:1 spike attenuation using C62.41 and C62.45 Category A and Category B tests. Noise Rejection: Common Mode - >120 dB, Normal Mode - >60dB				
Efficiency % (on-line)		85	88	90	91	90
Heat (on-line)	BTU/hr.	361	465	568	742	1896
	kW/hr.	0.106	0.136	0.166	0.217	0.556
Battery Charger (DC)		12V, 4A	12V, 4A	48V, 4A	48V, 4A	48V, 5A
Safety Certification		UL, CSA (CUL)				
EMI Compliance		FCC Class A				
Testing Standards		ANSI/IEEE C62.41 (1980); ANSI/IEEE C62.45 (1987); IEC 801-2, 801-4, 801-5				
Communication		DB25 communication port with RS-232 serial communications, alarm and inverter contact closures, and EPO shutdown.†				

Environmental

Operating Temperature		0° to 40° C				
Storage Temperature		-20° to +60° C (-20° to +40° C if battery not removed)				
Relative Humidity		5 to 95% without condensation				
Audible Noise (dBA)		48	50	50	51	52
Altitude		3050 m (10,000 ft.) maximum				

* 7 kVA model include front panel keypad and display. All specifications typical and are subject to change without notice.

UNITED STATES
8609 Six Forks Road
Raleigh, NC 27615 U.S.A.
Toll Free: 1.800.356.5794
or 919.872.3020

www.powerware.com

CANADA
Ontario: 416.798.0112

LATIN AMERICA
Argentina: 54.11.4343.6323
Brazil: 55.11.3616.8500
México: 52.55.5488.5252

EUROPE/MIDDLE EAST/AFRICA
Denmark: 45.3686.7910
Finland: 358.94.52.661
France: 33.1.6012.7400
Germany: 49.7841.666.0
Italy: 39.02.66.04.05.40
Norway: 47.23.03.65.50
Sweden: 46.8.598.940.00
United Kingdom: 44.1753.608.700

ASIA PACIFIC
Australia/NZ: 61.2.9693.9366
China: 86.21.6361.5599
HK/Korea/Taiwan: 852.2745.6682
India: 91.11.2649.9414 to 18
Singapore/SEA: 65.6829.8888

Powerware, LanSafe and FERRUPS are trade names, trademarks and/or service marks of Eaton Corporation or its subsidiaries and affiliates. All other trademarks are property of their respective owners.



Powerware

© 2006 Eaton Corporation
All Rights Reserved
Printed in USA
LTPO224
May 2006